

9913 Coax - RG-8/U Type

 	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
--	---

Description:

RG-8/U type, 10 AWG solid .108" bare copper conductor, semi-solid polyethylene insulation, Duobond II® + tinned copper braid shield (90% coverage), PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	8/U
AWG	10
Stranding	Solid
Conductor Diameter	.108 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	Semi-Solid PE - Semi-Solid Polyethylene
Insulation Diameter	.286 in.

OUTER SHIELD:

Outer Shield Material Trade Name	Duobond® II
Outer Shield Type	Tape/Braid

Outer Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1	Bonded DuoFoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	90

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.405 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +80°C
Non-UL Temperature Rating	75°C

9913 Coax - RG-8/U Type

Bulk Cable Weight	97 lbs/1000 ft.
Max. Recommended Pulling Tension	292 lbs.
Min. Bend Radius (Install)	6 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

SUITABILITY:

Suitability - Indoor	Yes
Suitability - Outdoor	Yes
Suitability - Aerial	Yes

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	89913

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	50 Ohms
Nom. Inductance	.059 μ H/ft
Nom. Capacitance Conductor to Shield	24.6 pF/ft
Nominal Velocity of Propagation	84 %
Nominal Delay	1.2 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	.9 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg.C	1.8 Ohms/1000 ft

Nom. Attenuation :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	5			.4
	10			.5
	50			1.0
	100			1.4
	200			1.8
	400			2.6
	700			3.6
	900			4.1
	1000			4.4
	1500			5.4
	1800			6.0
	2000			6.4
	2500			7.3
	3000			8.0
	4000			9.5

9913 Coax - RG-8/U Type

Max. Power Rating :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Max. Power Rating (W)
	5			4021
	10			3217
	50			1609
	100			1149
	200			894
	400			619
	700			447
	900			393
	1000			366
	1500			298
	1800			269
	2000			252
	2500			221
	3000			202
	4000			170

Max. Operating Voltage - Non-UL 300 V RMS

NOTES:

Notes Low Loss. Max. Operating Frequency: 8.5 GHz.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9913 010100	RG-8/U TYPE COAX	100	14.2	BLACK	C
9913 0101000	RG-8/U TYPE COAX	1000	116	BLACK	C
9913 010250	RG-8/U TYPE COAX	250	31.75	BLACK	C
9913 010500	RG-8/U TYPE COAX	500	57	BLACK	C

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 02-19-2007

9913 Coax - RG-8/U Type

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.